


Oxy Care Digi comes equipped with an Inbuilt Oxygen Sensor & Flow Sensor to indicate live display of Output Oxygen Purity & Flow Rate set on its Crystal Clear Large LCD Display Screen. Easy & Noiseless Operation with Wheels for easy maneuverability. Has a separate port for Nebulization & electronic fuse to prevent it from electrical surge. Although promoted as a 5 LPM Oxygen Concentrator, same equipment can be used with reduced oxygen purity at 6 & 7 LPM during emergency.

- ✓ Flow Rate: 1-5 LPM
- ✓ 93% +/- 3% Oxygen Purity up to 5 LPM
- ✓ Net Weight : 15.5 Kgs
- ✓ Sound Level: <54 db
- ✓ Inbuilt Nebulizer Port
- ✓ Digital Display to Indicate Oxygen Flow Rate & Oxygen Purity on a sharp large LCD Display
- ✓ Dimensions: 240x345x555 mm
- ✓ Power Consumption: 400 Watts
- ✓ ISO & CE Certified



 **+91-73388 84414**

 **+91-73388 84414**

OXY CARE PRIME
10 LPM OXYGEN CONCENTRATOR



Heavy Duty Oxygen Concentrator with Flow Rate capacity of 10 LPM. Equipped with Durable Compressors & Imported Sieve Membrane to provide Oxygen at Highest Purity of 93% +/- 3%. Inbuilt Nebulizer. Easily portable with wheels. Innovative storage compartment to keep Nasal Cannula's & all disposables. Quiet Working & Preset Timer functions. Power Failure, Low Pressure / High Pressure, Low Oxygen Alarms for Easy Error Diagnosis. Display indicates Accumulation, Switch, Operation Time & Output Pressure.

- ✓ Flow Rate: 0-10 LPM
- ✓ 93% +/- 3% Oxygen Purity
- ✓ Net Weight : 28 Kgs
- ✓ Sound Level: <50 db
- ✓ Inbuilt Nebulizer Port & Storage Compartment
- ✓ Display Indicates Switch Time, Accumulation Time, Working Time, Outlet Pressure.
- ✓ Dimensions: 365x375x600 mm
- ✓ Power Consumption: 550 Watts
- ✓ ISO & CE Certified

- ✓ Compact, Light Weight & Ultra Portable (0.9Kg).
- ✓ User Friendly with Ergonomically Designed Rotary Dial for all inputs.
- ✓ Therapy Data - AHI, Snoring Index, Usage Hours, P90, Leak, etc., can be easily viewed from the device itself from previous night sleep upto an year.
- ✓ Includes Easily Detachable Heated Humidifier.
- ✓ Bio Compatible Easy to Clean Stainless Steel Humidifier Tank.
- ✓ Real Time Therapy Data Display.
- ✓ Includes Automatic & Manual CPAP modes.
- ✓ Expiratory Pressure Relief available.
- ✓ Free SD card with Powerful Data Analysis Software.
- ✓ Free Comfo-Fit Nasal Mask with headgear.
- ✓ Easy to generate detailed printed reports for doctor's analysis.
- ✓ ISO, CE & IP 22 Certified Device.
- ✓ 2 Years Warranty.

Work Mode	CPAP, Auto CPAP
Therapy Data Display	AHI, SNI, Used Hours, etc for a period upto 1 year
Sound	<28 dB
Screen	2.4 inch Sharp LCD Display
Pressure Range	4-20 cm H2O
Data Storage	SD Card
EPR	Yes, 0-3 Level
Screen Auto Sleep	Yes
Power Supply	Input 100-240V, 50-60Hz, 1-2A; Output +24V, 2.5 A
DC Voltage	24VDC, 2.5A Maximum
Cooling Down	Available
Leak Alert	Yes
Filter Change Alert	Yes
Backup Rate	5-40/min, adjustable
Mask Matching	Yes
Ramp Time	0-60 min adjustable 5min/step
Auto ON/OFF	Yes
Tubing	Heated Tubing
Mask	Comfo Fit Nasal Mask
Travel Bag	Yes
Humidifier tank	Stainless Steel
Auto - Altitude	Yes
Leak Compensation	Yes
Awake Detection	Yes
Breathe Event Detection	Yes
Water Capacity	250ml Max
Humidifier Level	Heated, 0-5 Level & detachable
Colour	White
Dimensions(cm)	14Lx13Wx9H (main); 26Lx13Wx11H(with humidifier)
Weight	0.9Kg(Net weight); 1.5Kg (with humidifier)



ENTRUSTED
... Caring is our Calling

PRO-VENT ST-25
BiPAP NON INVASIVE VENTILATOR



+91-73388 84414

Work Mode	ST,S,T, CPAP
Therapy Data Display	AHI, SNI, Used Hours, etc for a period upto 1 year
Sound	<28 dB
Screen	2.4 inch Sharp LCD Display
Pressure Range	4-25 cm H2O
IPAP	4-25 cm H2O
EPAP	4-20 cm H2O
Data Storage	SD Card
Power Supply	Input 100-240V, 50-60Hz, 1-2A; Output +24V, 2.5 A
DC Voltage	24VDC, 2.5A Maximum
Cooling Down	Available
Leak Alert	Yes
Filter Change Alert	Yes
Backup Rate	5-40/min, adjustable
Mask Matching	Yes
Ramp Time	0-60 min adjustable 5min/step
Auto ON/OFF	Yes
Rise Time	100-900ms
Expiratory Sensitivity	Low, Medium, High
Inspiratory Sensitivity	Low, Medium, High
EPR	Yes, 0-3 Level
Auto - Altitude	Yes
Leak Compensation	Yes
Awake Detection	Yes
Breathe Event Detection	Yes
Water Capacity	250ml Max
Humidifier Level	Heated, 0-5 Level & detachable
Colour	Black
Dimensions(cm)	14Lx13Wx9H (main); 26Lx13Wx11H(with humidifier)
Weight	0.9Kg(Net weight); 1.5Kg (with humidifier)

- ✓ Compact, Light Weight & Ultra Portable (0.9Kg)
- ✓ User Friendly with Ergonomically Designed Rotary Dial for all inputs.
- ✓ Therapy Data - AHI, Snoring Index, Usage Hours, P90, Leak, etc., can be easily viewed from the device itself from previous night sleep upto an year.
- ✓ Includes Easily Detachable Heated Humidifier.
- ✓ Bio Compatible Easy to Clean Stainless Steel Humidifier Tank.
- ✓ Real Time Therapy Data Display.
- ✓ Includes S/T mode with Pressure Range of 4 - 25 cm h2o.
- ✓ Free SD card with Powerful Data Analysis Software.
- ✓ Free Comfo-Fit Full Face Mask with headgear.
- ✓ Easy to generate detailed printed reports for doctor's analysis.
- ✓ ISO, CE & IP 22 Certified Device.
- ✓ 2 Years Warranty



ENTRUSTED
... Caring is our Calling

OXY CARE PLUS
5 LPM OXYGEN CONCENTRATOR



Specifications:
Flow rate: 0-5 LPM
Outlet pressure: 0.04-0.07 MPA
Weight: 16Kgs | Size: 348*280*510 mm
Sound level ≤ 40 db Inbuilt nebulizer kit

Feel the comfort of easy oxygen intake with Entrusted Oxygen Concentrators which delivers oxygen at a flow rate of 0 - 5 liters per minute. Our equipment delivers oxygen at a purity of 93 % ± 3%. Our oxygen concentrator is designed with heavy duty compressors specially considering the voltage fluctuations in India. It comes with an added advantage that the premium quality zeolite from United States and France are being used to adsorb the nitrogen content in the atmospheric air. It comes with an innovative big LCD display and low noise which extends your comfort zone.

Anticipating your inevitable need of a nebulizer with an oxygen concentrator, we offer you built in nebulizer kit with our equipment.

Our LCD display parameters include switch times, operating pressure, present working time, accumulated working time, presetting time from 10 minutes to 40 hours.

It alerts you with an alarm during power failure, high and low pressure, low purity/low flow, high temperature, maintenance.

OXY CARE SMART
FULLY PORTABLE WITH BATTERY & CAR ADAPTER



Technical Parameter:
Oxygen Flow (L/min) 1-5
Oxygen Purity (%) 93%±3% (1LPM) ,
75%±3% (2LPM) ,55%±3% (3LPM)
45%±3% (4LPM) ,38%±3% (5LPM)
Oxygen Pressure (Mpa) 0.03-0.07 Noise (dB) ≤45
Dimension(mm)350×190×320
N.W. 6 kg. Rated Power (W)≤75
Power Supply - AC220V

Our portable oxygen concentrator whose oxygen output is 1-5L/min is small and light. Therefore, it is quite suitable for mobile use. Combined with an adaptor for vehicle, this oxygen producing machine can be mounted on automobiles. With rechargeable battery, this machine can be used when people travel. This is a cost-effective product appropriate for blue-and-white collar workers and the common masses.

The concentration of the oxygen produced by our product is adjustable within the range of 30%-90%. When producing oxygen with concentration of 90% and flow rate of 1L/min, this portable oxygen generation plant is suitable for people who need to inhale high-concentration low-flow oxygen, such as patients with carbon dioxide retention. When producing oxygen with concentration of 30% and flow rate of 5L/min, our portable oxygen concentrator is appropriate for people who need to inhale low-concentration high-flow oxygen, for example, athletes.

Application:

- This portable oxygen concentrator offers a great outdoor oxygen supply solution for patients who have to go out for a short time;
- This portable oxygen concentrator can be used to cure headache and sleep apnea syndrome caused by cervical spondylosis;
- Inhaling oxygen with this oxygen gas generator will help white-collar workers and students to regain energy;
- This portable oxygen concentrating equipment is available for home health care of pregnant women or old people;
- It helps relieve discomfort caused by haze;
- Suitable for oxygen cocktail making;

+91-73388 84414